

Listing of All Claims Including Current Amendments

1-6 (Cancelled)

7. (Currently amended) An apparatus for treating a particulate material, comprising:

- a container having a base, an upright wall widening ~~from bottom to top~~ in an upward direction, and a deflection element adjoining said wall in an upper region of said container in order to deflect a direction of movement of said material;
- said wall being rotatable about a vertical axis of rotation;
- an opening for placing particulate material in to the container;
- ~~at least a first air gap in an upper portion of the wall that transitions from said wall to said deflection element; and~~
- an air feed device for feeding an air stream through said ~~at least one first air gap into said container, at least one of said first air gap and said air feed device being configured such that said air stream introduced through said first air gap has a flow component oriented substantially in an upward direction from bottom to top and, in a region adjoining said air gap, oriented substantially tangentially with respect to the course of~~ at least one of said wall and said deflection element.

8. (Currently amended) The apparatus of claim 7, wherein, in said ~~upper portion of transition region from said wall that transitions from said wall to said deflection element, there is at least a second air gap which is spaced apart vertically from said first air gap, at least one of said second air gap and said air feed device being configured such that an air stream fed in by said air feed device has a flow component oriented substantially in an upward direction from bottom to top and, in a region adjoining said~~

second air gap, oriented substantially tangentially with respect to ~~the course of~~ at least one of said wall and said deflection element.

9. (Cancelled).

10. (Original) The apparatus of claim 7, wherein said deflection element has a first section which directly adjoins said wall, said first air gap being present between an upper end of said wall and a lower end of said first section.

11. (Currently amended) The apparatus of claim 10, wherein said first section widens in an upward direction from bottom to top with a shape accommodating the shape of said wall in a region of said upper end of said wall.

12. (Original) The apparatus of claim 7, wherein said deflection element has a first section which directly adjoins said wall, said first air gap being present between an upper end of said wall and a lower end of said first section, and wherein said first section does not corotate with said wall.

13. (Currently amended) The apparatus of claim 7, wherein, in said upper portion of transition region from said wall that transitions from said wall to said deflection element, there is ~~at least~~ a second air gap, which is spaced apart vertically from said first air gap, and wherein said deflection element has a first section which directly joins said wall, wherein said deflection element has at least a second section, and wherein said second air gap is arranged between an upper end of said first section and a lower end of said second section.

14. (Original) The apparatus of claim 13, wherein said second section, as viewed from a center of said container, is curved concavely, and wherein said lower end of said second section adjoins said upper end of said first section with a form fit.

15. (Currently amended) The apparatus of claim 7, wherein, in said ~~upper portion of transition region from said wall that transitions from said wall to said deflection element~~, there is ~~at least~~ a second air gap, which is spaced apart vertically from said first air gap, and wherein said deflection element has a first section which directly joins said wall, wherein said deflection element has at least a second section, and wherein said second air gap is arranged between an upper end of said first section and a lower end of said second section, and wherein said second section does not corotate with said wall.

16. (Currently amended) The apparatus of claim 7, wherein said deflection element is air-permeable over a subregion which follows said ~~at least one~~ first air gap.

17. (Currently amended) The apparatus of claim 7, wherein a width of said ~~at least one~~ first air gap is adjustable.

18. (Currently amended) The apparatus of claim 7, wherein adjustable guide elements are arranged at said ~~at least one~~ first air gap.

19. (Currently amended) The apparatus of claim 7, wherein said base has ~~at least one~~ an air gap, and wherein an air feed device is provided for said base, at least one of said ~~at least~~ air gap in said base and said air feed device for said base being configured in such a way that said air stream introduced through said air gap in said base has a

flow component oriented substantially tangentially with respect to said base and toward said wall.

20. (Original) The apparatus of claim 19, wherein said base is constructed from a plurality of concentric ring elements with different diameters, which are arranged in layers partly overlapping one another radially and between which a plurality of air gaps form.

21. (Currently amended) The apparatus of claim 7, wherein said base has ~~at least one~~one air gap, and wherein a width of said ~~at least one~~ air gap in said base can be adjusted.

22. (Currently amended) The apparatus of claim 7, wherein said base has ~~at least one~~one air gap, and wherein said ~~at least one~~ air gap in said base opens automatically when being acted on with an air stream and closes when said air stream is switched off.

23. (Currently amended)The apparatus of claim 7, wherein said base has ~~at least one~~one air gap and wherein said base has air guide elements which additionally impart to an air stream introduced through said ~~at least one~~ air gap in said base a flow component oriented in a direction of rotation of said wall.

24. (Original)The apparatus of claim 7, wherein said base does not corotate with said wall.

25. (Currently amended)The apparatus of claim 7, wherein said container has a return surface that tapers in a downward direction from top to bottom, on which said material deflected by said deflection element is moved back downward to said base.

26. (Currently amended) The apparatus of claim 25, wherein said return surface is supported on said wall via a sliding ring bearing in such a way that said return surface does not corotate with said wall or rotates with a rotational speed lower than ~~the~~ rotational speed of said wall.

27. (Original) The apparatus of claim 7, wherein said container has a return surface which is constructed from a plurality of concentric ring elements, which partly overlap one another and between which a plurality of air gaps form.

28. (Currently amended) The apparatus of claim 27, wherein said air gaps in said return surface are configured in such a way that an air stream introduced through said air gaps has a flow component oriented in a downward direction from top to bottom and substantially parallel to ~~the course of~~ said return surface.

29. (Currently amended) The apparatus of claim 7, wherein a spraying device for spraying said material with a moist covering medium is arranged in said container and has an annular gap nozzle, said nozzle being arranged upright in said container, and said covering medium and spraying air being fed into said nozzle in an upward direction from bottom to top, and wherein said nozzle is acted on from above with an additional air stream.

30. (New) An apparatus for treating a particulate material, comprising:

- a container having a base, an upright wall widening in an upward direction, and a deflection element adjoining said wall in an upper region of said container in order to deflect a direction of movement of said material;
- said wall being rotatable about a vertical axis of rotation;
- an opening for placing particulate material in to the container;

- a first air gap in an upper portion of the wall that transitions from said wall to said deflection element;

- an air feed device for feeding an air stream through said first air gap into said container, at least one of said first air gap and said air feed device being configured such that said air stream introduced through said first air gap has a flow component oriented substantially in an upward direction and, in a region adjoining said air gap, oriented substantially tangentially with respect to at least one of said wall and said deflection element; and

- a second air gap which is spaced apart vertically from said first air gap, wherein said air feed device has a first feed duct for feeding a first air stream to said first air gap, and at least a second feed duct, separated from said first feed duct, for feeding a second air stream to said second air gap.

31. (New) The apparatus of claim 30, wherein at least one of said second air gap and said air feed device being configured such that an air stream fed in by said air feed device has a flow component oriented substantially in an upward direction and, in a region adjoining said second air gap, oriented substantially tangentially with respect to at least one of said wall and said deflection element.

32. (New) The apparatus of claim 30, wherein said deflection element has a first section that adjoins said wall and a second section that adjoins said first section, wherein said first air gap is between an upper end of said wall and a lower end of said first section, and wherein said second air gap is arranged between an upper end of said first section and a lower end of said second section.

33. (New) The apparatus of claim 32, wherein said first section or said second section do not corotate with said wall.

34. (New) The apparatus of claim 32, wherein said first section widens in an upward direction with a shape accommodating the shape of said wall in a region of said upper end of said wall, and wherein said second section, as viewed from a center of said container, is curved concavely.

35. (New) An apparatus for treating a particulate material, comprising:

- a container having a base, an upright wall widening in an upward direction, and a deflection element adjoining said wall in an upper region of said container in order to deflect a direction of movement of said material;

- said wall being rotatable about a vertical axis of rotation;

- an opening for placing particulate material in to the container;

- a first air gap in an upper portion of the wall that transitions from said wall to said deflection element, said first air gap forming either an interrupted or uninterrupted annular gap that encompasses the vertical axis of rotation; and

- an air feed device for feeding an air stream through said first air gap into said container, at least one of said first air gap and said air feed device being configured such that said air stream introduced through said first air gap has a flow component oriented substantially in an upward direction and, in a region adjoining said air gap, oriented substantially tangentially with respect to at least one of said wall and said deflection element.